



Level 41, Emirates Towers, PO Box 31303-Dubai. UAE



Transparent Glass Display



Technical Specifications

Model No.	P3	P3.9	P5	P7.8	P10	P16	P20
Pixel Pitch	3.12-6.25 mm	3.9-7.8 mm	5.2mm	7.8 mm	10.4 mm	15.6 mm	20 mm
Module Size	1000x500 x30 mm	1000x500 x30 mm	1000x500 x30 mm	1000x500 x30 mm	1000x500 x30 mm	1000x500 x30 mm	1000x500 x30 mm
Brightness	6000 nits	6000 nits	6000 nits	6000 nits	6000 nits	5500 nits	5500 nits
Transparency	>73%	>76%	>76%	>81%	>84%	>87%	>90%
Module Resolution	320x80 px	256x64 px	190x80 px	128x64 px	100x50 px	64x32 px	48x24 px
Resolution	51,200 dot/m2	32,768 dot/m2	32,026 dot/m2	16,384 dot/m2	9,216 dot/m2	4,026 dot/m2	2,304 dot/m2
Ingress Protection	IP20	IP20	IP20	IP20	IP20	IP20	IP20
Refresh Rate	3840 Hz	3840 Hz	3840 Hz	3840 Hz	3840 Hz	3840 Hz	3840 Hz
Viewing Angle	120°	120°	120°	120°	120°	120°	120°
Minimum Viewing Distance	3 meters	3 meters	5 meters	8 meters	10 meters	15 meters	20 meters
Video Signal Input	HDMI/DVI	HDMI/DVI	HDMI/DVI	HDMI/DVI	HDMI/DVI	HDMI/DVI	HDMI/DVI
Temperature range	-10 to 40°C	-10 to 40°C	-10 to 40°C	-10 to 40°C	-10 to 40°C	-10 to 40°C	-10 to 40°C
Power Supply	UL Certified	UL Certified	UL Certified	UL Certified	UL Certified	UL Certified	UL Certified
Av. Power Consumption	260 w/m ²	260 w/m ²	260 w/m ²	260 w/m ²	260 w/m ²	260 w/m ²	260 w/m ²



04 3132817



sales@umh.ae



www.umh.ae